

Refining: Continuous Level

Company Name: _____

Customer Contact Name: _____

Customer Address: _____

Phone and Fax: _____

City, State, Zip: _____

Cell: _____

Sales Person/Rep.: _____

Email: _____

Representative Firm: _____

RFQ (request for quotation): _____

Process Name/Description: _____

Tag Number: _____

Process Material*: _____

Dielectric Constant: _____

*What is the pour point? _____

Specific Gravity: _____ °F °C

Process Information

1. Process Temperature Range: Min: _____ Max: _____ °F °C

2. Process Pressure Range: Min: _____ Max: _____ psig bar

3. Area Classification: General Purpose Class 1 Div. 1 Class 1 Div. 2

4. Liquid Buildup on Vessel Walls: No Yes – Thickness: _____ in mm other _____

5. Agitation/Turbulent Vessel: No Yes – RPM, if known: _____

6. Liquid surface condition – does bubbling and/or sublimation occur? _____

7. Foam Layer Height: _____ in mm other _____

8. Must measure foam height? No Yes - type of foam: Water-based Hydrocarbon

9. Interface: No Yes Upper dK: _____ Lower dK: _____

10. Fully Submerged Probe: No Yes - FX81 can be used.

11. Is the process heat-traced? No Yes - type: 150# Steam 450# Steam Electric Other

12. Will level change be faster than 3 ft/min? No Yes

Vessel

Please provide a detailed drawing/sketch of the vessel on the reverse side of the form.

13. Vessel Height: _____ in ft other _____

14. Vessel Diameter/Width: _____ in ft other _____

15. Shape of Vessel:      Other: Please Sketch

16. Shape of Vessel Bottom: Flat Dished

17. Vessel Material of Construction: 316 SS Carbon Steel Glass-lined Plastic Other

18. Is the vessel lined? No Yes – material: _____

19. Where is the process connection located? _____

20. Size/Type of Process Connection: _____

21. Is the guided microwave radar probe contained in an external chamber? No Yes (Recommended min. diameter is 3")

22. What is the pipe schedule? _____

23. Obstructions in the Vessel: No Yes what is the obstruction? _____

24. Vessel Wall Surface Finish: _____

Sensor/Probe

25. Preferred/Specified Probe Material: _____

26. Probe Type: Cable Rod Coaxial (Not recommended in bridles or applications prone to buildup)

27. Is overhead clearance adequate for installation of gauge and antenna system? Yes No

28. Sensor Type: 2-wire 4-wire Other _____

29. Communication Protocol: 4...20mA/HART Fieldbus – Host system: _____

30. Output Settings: Standard/4...20mA Other _____

31. Failure Mode upon Loss of Level Signal: 22mA 3.6mA Hold Last Value

32. Preferred Sensor Transmitter: _____

33. Power Input: _____

34. Display: Remote Integral None

35. Display Value: Distance Level Percent Other _____

36. Relay: No Yes – quantity: _____

Vessel Data

Please answer the questions related to the vessel that most closely represents your application.

Bridle Application

37. Distance from Bridle Flange to 100% Line (A): _____

38. Distance from Bridle Flange to 0% Line (B): _____

39. Distance from Tap to Tap (C): _____

40. Distance from Bridle Flange to Top Tap (D): _____

Tank Application

41. Distance from Flange to 100% Line (E): _____

42. Distance from Flange to 0% Line (F): _____

43. Height of the Mounting Nozzle (G): _____

44. Distance from Vessel Top to 100% Line (H): _____

Application or Vessel Sketch