

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:	IECEx TUR 14.0007X	Page 1 of 4	Certificate history:
Status:	Current	Issue No: 2	Issue 1 (2021-05-28) Issue 0 (2014-05-12)
Date of Issue:	2024-05-28		
Applicant:	VEGA Grieshaber KG Am Hohenstein 113 77761 Schiltach Germany		
Equipment:	VEGABOX 03, type BOX03(*).*C/*O******		
Optional accessory:			
Type of Protection:	Ex ia		
Marking:	Ex ia IIC T6 T1 Ga or Gb		
Approved for issue of Certification Body:	n behalf of the IECEx	Christian Mehrhoff	
Position:		Assigned certifier	
Signature: (for printed version)		Alin All	lap
Date: (for printed version)		2024-05-28	P
This certificate is not	chedule may only be reproduced in full. transferable and remains the property of the issuing body enticity of this certificate may be verified by visiting www.ie	r. cex.com or use of this QR Code.	
Certificate issued	by:		A
TUV Rheinland Am Grauen Stein Cologne	d Industrie Service GmbH n	T	



iny

IECEX		IECEx Certifica of Conformity	
Certificate No.:	IECEx TUR 14.0007X	Page 2 o	f 4
Date of issue:	2024-05-28	Issue No	: 2
Manufacturer:	VEGA Grieshaber KG Am Hohenstein 113 77761 Schiltach Germany		
Manufacturing locations:	VEGA Grieshaber KG Am Hohenstein 113 77761 Schiltach Germany	VEGA India Level and Pressure Measurement Pvt. Ltd. Plot No. 1, Gat No. 181, Village - Phulgaon, Tal. Haveli Pune 412216 India	VEGA Americas, Inc. 3877 Mason Research Parkway Ohio Mason 45036 United States of America

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements Edition:7.0

IEC 60079-11:2023 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i" Edition:7.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

DE/TUR/ExTR14.0007/02

Quality Assessment Report:

DE/TUN/QAR06.0002/13



Certificate No.: **IECEx TUR 14.0007X**

2024-05-28

Date of issue:

Page 3 of 4

Issue No: 2

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The VEGABOX 03 is preferably used for field mounting for separated connection of sensor circuits and as breather housing. The VEGABOX 03 of type series VEGABOX 03 with integrated connection terminals are preferably used for pressure compensation of the pressure measuring cell and as terminal box in conjunction with pressure transmitters of Messrs. VEGA in the cable version with capillary cable.

In VEGABOX 03 only terminal blocks as type VEGABOX 03 for connection of intrinsically safe circuits can be installed. A terminal block is preferably used for connection of an inrinsically safe circuit of VEGA pressure transmitters in the version with connection cable with corresponding power supply or signal conditioning instrument.

The VEGABOX 03 is an intrinsically safe electrical instrument for installation in hazardous areas with combustible gases, mist or vapour, requiring instruments of category EPL Ga or EPL Gb or for installation outside of hazardous areas. The VEGABOX 03 is an intrinsically safe instrument for installation in hazardous areas of all combustible materials of explosion group IIA, IIB and IIC.

If the VEGABOX 03 are installed and operated in hazardous areas, the general Ex installation regulations EN 60079-14 as well as these safety instructions must be observed.

SPECIFIC CONDITIONS OF USE: YES as shown below:

1. Risk of electrostatic discharge, Avoid friction, no dry cleaning and don't install this device in areas with flowing, non-conductive products, The safety instruction of the manufacturer must be observed.

2. The enclosure may only get into contact with products which it is resistant to. The safety instruction of the manufacturer must be observed.



Certificate No .:

IECEx TUR 14.0007X

Date of issue:

2024-05-28

Page 4 of 4

Issue No: 2

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

• Update to the latest IEC 60079-11 edition 7.0: 2023

- Removal of IEC 60079-26 edition 4.0: 2021
- · Adjustment of model code
- Addition of new manufacturing location
- · Update of safety instructions

Annex:

Attachment IECEx_TUR_14.0007X_002_1.pdf



Device:
Type:Breather housing
VEGABOX03, type BOX03(*).*C/*O*****Manufacturer:VEGA Grieshaber KGAddress:Am Hohenstein 113
77761 Schiltach, Germany

Technical data

Supply and signal circuit:	
Terminals 1, 2	In type of protection intrinsic safety Ex ia IIC/IIB
	For connection to a certified, intrinsically safe circuit.
	Maximum values:
	• Ui = 30 V
	• li = 150 mA • Pi = 1000 mW
	$\bullet PI = 1000 \text{ mW}$ $\bullet Ci = 0$
	• Li = 0
	When using the supplied connection cable, the following cable inductances L_i^{\prime} and cable capacitances C_i^{\prime} have to be taken into account:
	• Li = 0.6 μH/m
	• C _{i wire/wire} = 133 pF/m • C _{i wire/screen} = 215 pF/m
Temperature measuring circuit:	
Terminals 3, 4, 5, 6	In type of protection intrinsic safety Ex ia IIC/IIB
	For connection to a certified, intrinsically safe circuit.
	Maximum values:
	• Ui = 30 V
	●li = 100 mA ●Pi = 500 mW
	• Ci = 0
	• Li = 0
	When using the supplied connection cable, the following cable inductances L_i^{\prime} and cable capacitances C_i^{\prime} have to be taken into account:
	● Li = 0.6 μH/m
	● C _{i wire/wire} = 188 pF/m ● C _{i wire/screen} = 555 pF/m

The intrinsically safe circuits are electrically isolated from each other and from parts which can be grounded.



EPL Ga instrument

Temperature class	T6 T1
Permissible ambient temperature	-20 +60 °C

The connection housing must only be operated in a hazardous area requiring EPL Ga instruments if there are atmospheric conditions (pressure of 0.8 bar to 1.1 bar). If there is no explosive atmosphere, then the permissible operating temperatures and pressures must be taken from the manufacturer specifications.

EPL Gb instrument

Temperature class	T6 T1
Permissible ambient temperature	-50 +80 °C

The permissible operating temperatures without explosion-endangered atmosphere are mentioned in the respective manufacturer instructions, e.g. operating instructions manuals.

		of Conformity	
	IEC Certification Sys	CTROTECHNICAL COMMISSION tem for Explosive Atmospheres the IECEx Scheme visit www.iecex.com	
Certificate No.:	IECEx TUR 14.0007X	Page 1 of 4	Certificate history
Status:	Current	Issue No: 1	Issue 0 (2014-05
Date of Issue:	2021-05-28		
Applicant:	VEGA Grieshaber KG Am Hohenstein 113 77761 Schiltach Germany		
Equipment:	VEGABOX 03, type BOX03.IC/IO******		
Optional accessory:			
Type of Protection:	Ex ia		
Marking:	Ex ia IIC T6 T1 Ga or Gb		
	on behalf of the IECEx	Christian Mehrhoff	
Approved for issue o Certification Body: Position:	on behalf of the IECEx		1 hi
Certification Body: Position: Signature:	on behalf of the IECEx	~	laAl
Certification Body: Position:	on behalf of the IECEx		laft
Certification Body: Position: Signature: (for printed version) Date: 1. This certificate and s 2. This certificate is not	on behalf of the IECEx schedule may only be reproduced in full. transferable and remains the property of the issuin enticity of this certificate may be verified by visiting	Assigned certifier	leftj Istori
Certification Body: Position: Signature: (for printed version) Date: 1. This certificate and s 2. This certificate is not	schedule may only be reproduced in full. transferable and remains the property of the issuin enticity of this certificate may be verified by visiting	Assigned certifier	
Certification Body: Position: Signature: (for printed version) Date; 1. This certificate and s 2. This certificate is not 3. The Status and auth Certificate issued	schedule may only be reproduced in full. I transferable and remains the property of the issuin enticity of this certificate may be verified by visiting d by: Industrie Service GmbH	Assigned certifier	
Certification Body: Position: Signature: (for printed version) Date: 1. This certificate and s 2. This certificate is not	schedule may only be reproduced in full. t transferable and remains the property of the issuin	Assigned certifier	le fij



-		
Certificate No.:	IECEx TUR 14.0007X	Page 2 of 4
Date of issue:	2021-05-28	Issue No: 1
Manufacturer:	VEGA Grieshaber KG Am Hohenstein 113 77761 Schiltach Germany Germany	
Additional manufacturing locations:	VEGA Americas, Inc 4241 Allendorf Drive Cincinnati, Ohio 45209 United States of America	
IEC Standard list bel found to comply with	ow and that the manufacturer's quality system	tative of production, was assessed and tested and found to comply with the n, relating to the Ex products covered by this certificate, was assessed and certificate is granted subject to the conditions as set out in IECEx Scheme
STANDARDS : The equipment and a to comply with the fo		schedule of this certificate and the identified documents, was found
IEC 60079-0:2017 Edition:7.0	Explosive atmospheres - Part 0: Equipmen	t - General requirements
IEC 60079-11:2011 Edition:6.0	Explosive atmospheres - Part 11: Equipme	nt protection by intrinsic safety "i"
IEC 60079-26:2021-02 Edition:4.0	Explosive atmospheres - Part 26: Equipme	nt with Separation Elements or combined Levels of Protection
		pliance with safety and performance requirements included in the Standards listed above.
TEST & ASSESSME A sample(s) of the ec		nination and test requirements as recorded in:
Test Report:		
DE/TUR/ExTR14.00	07/01	
Quality Assessment	Report:	
DE/TUN/QAR06.000	2/10	



Certificate No... IECEx TUR 14.0007X

Date of issue:

Page 3 of 4 Issue No: 1

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

2021-05-28

The VEGABOX 03 is preferably used for field mounting for separated connection of sensor circuits and as breather housing. The VEGABOX 03 of type series VEGABOX 03 with integrated connection terminals are preferably used for pressure compensation of the pressure measuring cell and as terminal box in conjunction with pressure transmitters of Messrs. VEGA in the cable version with capillary cable.

In VEGABOX 03 only terminal blocks as type VEGABOX 03 for connection of intrinsically safe circuits can be installed. A terminal block is preferably used for connection of an inrinsically safe circuit of VEGA pressure transmitters in the version with connection cable with corresponding power supply or signal conditioning instrument.

The VEGABOX 03 is an intrinsically safe electrical instrument for installation in hazardous areas with combustible gases, mist or vapour, requiring instruments of category EPL Ga or EPL Gb or for installation outside of hazardous areas. The VEGABOX 03 is an intrinsically safe instrument for installation in hazardous areas of all combustible materials of explosion group IIA, IIB and IIC.

If the VEGABOX 03 are installed and operated in hazardous areas, the general Ex installation regulations EN 60079-14 as well as these safety instructions must be observed.

SPECIFIC CONDITIONS OF USE: YES as shown below:

1. Risk of electrostatic discharge. Avoid friction, no dry cleaning and don't install this device in areas with flowing, non-conductive products. The safety instruction of the manufacturer must be observed.

2. The enclosure may only get into contact with products which it is resistant to. The safety instruction of the manufacturer must be observed.



Certificate No.: **IECEx TUR 14.0007X** Page 4 of 4

Date of issue:

2021-05-28

Issue No: 1

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

- · Minor adjustments of manuals
- Minor adjustment of type designation
 Standard update of IEC 60079-0 and 60079-26, checklists omitted since there are no applicable major technical changes

Annex:

Attachment IECEx_TUR_14.0007X_001.pdf



Supply and signal circuit:	
Terminals 1, 2	In type of protection intrinsic safety Ex ia IIC/IIB
	For connection to a certified, intrinsically safe circuit.
	Maximum values:
	• Ui = 30 V
	• li = 150 mA • Pi = 1000 mW
	\bullet Ci = 0
	• Li = 0
	When using the supplied connection cable, the following cable in- ductances L' and cable capacitances C' have to be taken into account:
	•Li = 0.6 μH/m
	• C _{i wirdwire} = 133 pF/m
	• C _{i wire/screen} = 215 pF/m
Temperature measuring circuit:	
Terminals 3, 4, 5, 6	In type of protection intrinsic safety Ex ia IIC/IIB
	For connection to a certified, intrinsically safe circuit.
	Maximum values:
	• Ui = 30 V
	•li = 100 mA •Pi = 500 mW
	$\bullet Ci = 0$
	• Li = 0
	When using the supplied connection cable, the following cable in- ductances L _i ' and cable capacitances C _i ' have to be taken into account:
	• Li = 0.6 μH/m
	• C _{i wire/wire} = 188 pF/m
	• C _{i wie/screen} = 555 pF/m

The intrinsically safe circuits are electrically isolated from each other and from parts which can be grounded.

EPL Ga instrument

Temperature class	T6 T1
Permissible ambient temperature	-20 +60 °C

The connection housing must only be operated in a hazardous area requiring EPL Ga instruments if there are atmospheric conditions (pressure of 0.8 bar to 1.1 bar). If there is no explosive atmosphere, then the permissible operating temperatures and pressures must be taken from the manufacturer specifications.

EPL Gb instrument

Temperature class	T6 T1
Permissible ambient temperature	-50 +80 °C

The permissible operating temperatures without explosion-endangered atmosphere are mentioned in the respective manufacturer instructions, e.g. operating instructions manuals.



INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No .:	IECEx TUR 14.0007X	issue No.:0	Certificate history:
Status:	Current		
Date of Issue:	2014-05-12	Page 1 of 3	
Applicant:	VEGA Grieshaber KG Am Hohenstein 113 77761 Schiltach Germany Germany		
Electrical Apparatus: Optional accessory:	VEGABOX BOX03.IO*****		
Type of Protection:	Ex ia		
Marking:	Ex ia IIC T6 T1 Ga or G	Bb	
Approved for issue on bet Certification Body:	alf of the IECEx	DiplIng. Klauspeter Graffi	
Position:		Head of Certification Body	
Signature: (for printed version) Date:		Reampet 12 2014-65-11	
1. This certificate and sch	edule may only be reproduce	ed in full.	

This certificate is not transferable and remains the property of the issuing body.
 The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

TUV Rheinland Industrie Service GmbH Am Grauen Stein 51105 Cologne Germany







Certificate No.: Date of Issue: IECEx TUR 14.0007X

2014-05-12

Issue No.: 0 Page 2 of 3

Manufacturer:

VEGA Grieshaber KG Am Hohenstein 113 77761 Schiltach Germany Germany

Additional Manufacturing location

(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2011 Edition: 6.0	Explosive atmospheres - Part 0: General requirements
IEC 60079-11 : 2011 Edition: 6.0	Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "
IEC 60079-26 : 2006 Edition: 2	Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report: DE/TUR/ExTR14.0007/00

Quality Assessment Report:

DE/TUN/QAR06.0002/05



Certificate No .:

IECEx TUR 14.0007X

Date of issue:

2014-05-12

Issue No.: 0

Page 3 of 3

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The VEGABOX 03 is preferably used for field mounting for separated connection of sensor circuits and as breather housing. The VEGABOX 03 of type series VEGABOX BOX03.IC/IO****** with integrated connection terminals are preferably used for pressure compensation of the pressure measuring call and as terminal box in conjunction with pressure transmitters of Messrs. VEGA in the cable version with capillary cable. In VEGABOX 03 only terminal blocks as type VEGABOX BOX03.IC/IO***** for connection of intrinsically safe circuits and the sense of th

In VECABUX 03 only terminal block is are type VEGABOX BOX03.IC/IO****** for connection of intrinsically safe circuits can be installed. A terminal block is preferably used for connection of an infiniscially safe circuit of VEGA pressure transmitters in the version with connection cable with corresponding power supply or signal conditioning instrument. The VEGABOX BOX03.IC/IO****** is an intrinsically safe electrical instrument for installation in hazardous areas with combustible gases, mist or vapour, requiring instruments of category EPL-Ga or EPL-Gb or for installation in hazardous areas of hazardous areas. The VEGABOX BOX03.IC/IO****** is an intrinsically safe instrument for installation in hazardous areas of all combustible materials of explosion group IIA, IIB and IIC.

CONDITIONS OF CERTIFICATION: YES as shown below:

1. Risk of electrostatic discharge. Avoid friction, no dry cleaning and don't install this device in areas with

flowing, non-conductive products. The safety instruction of the manufacturer must be observed.

The enclosure may only get into contact with products which it is resistant to. The safety instruction of the manufacturer must be observed.

Annex: DE-IECEx_TUR_14.0007X_00_Attachment_20140512.pdf



Attachment to Certificate IECEx TUR 14.0007 X Revison 0

Attachment to to Certificate IECEx TUR 14.0007/00 X

Device: Breather housing VEGABOX BOX03.IC/IO******

Manufacturer: VEGA Grieshaber KG

Address: Am Hohenstein 113 77761 Schiltach Germany

General product information:

The VEGABOX 03 is preferably used for field mounting for separated connection of sensor circuits and as breather housing. The VEGABOX 03 of type series VEGABOX BOX03.IC/IO****** with integrated connection terminals are preferably used for pressure compensation of the pressure measuring cell and as terminal box in conjunction with pressure transmitters of Messrs. VEGA in the cable version with capillary cable. In VEGABOX 03 only terminal blocks as type VEGABOX BOX03.IC/IO****** for connection of intrinsically safe circuits can be installed. A terminal block is preferably used for connection cable with corresponding power supply or signal conditioning instrument. The VEGABOX BOX03.IC/IO****** is an intrinsically safe electrical instrument for installation in hazardous areas with combustible gases, mist or vapour, requiring instruments of category EPL-Ga or EPL-Gb or for installation outside of hazardous areas. The VEGABOX BOX03.IC/IO****** is an intrinsically safe instrument for installation and intrinsically safe or for installation outside of hazardous areas. The VEGABOX BOX03.IC/IO******* is an intrinsically safe instruments of category EPL-Ga or EPL-Gb or for installation outside of hazardous areas. The VEGABOX BOX03.IC/IO****** is an intrinsically safe instrument for installation and areadous areas of all combustible materials of explosion group IIA. IIB and IIC.



In version VEGABOX BOX03.IC/IO****** with terminal blocks

Permissible ambient temperatures depending on temperature class

EPL-Ga instrument

Temperature class	T6 T1
Permissible ambient temperature	-20+60 °C

The connection housing must only be operated in a hazardous area requiring instruments of category EPL-Ga if there are atmospheric conditions (pressure of 0.8 bar to 1.1 bar). If there is no explosive atmosphere, then the permissible operating temperatures and pressures must be taken from the manufacturer specifications.

EPL-Gb instrument

Temperature class	T6 T1
Permissible ambient temperature	-50 +80 °C

The permissible operating temperatures without explosion-endangered atmosphere are mentioned in the respective manufacturer instructions, e.g. operating instructions manuals.