

Translation

(1) EC-Type-Examination Certificate

- (2) Equipment and protective systems intended for use in potentially explosive atmospheres, **Directive 94/9/EC**



- (3) **Certificate Number** TÜV 14 ATEX 145373

- (4) for the equipment: Signal conditioning instruments type
VEGATOR TOR 141.A C/O/U X****
VEGATOR TOR 141.A C/O/U S****
VEGATOR TOR 142.A C/O/U *****

- (5) of the manufacturer: VEGA Grieshaber KG

- (6) Address: Am Hohenstein 113
77761 Schiltach
Germany

Order number: 8000437160


Date of issue: 2014-10-22

- (7) The design of this equipment or protective system and any acceptable variation thereto are specified in the schedule to this EC-Type-Examination Certificate and the documents therein referred to.
- (8) The TÜV NORD CERT GmbH, notified body No. 0044 in accordance with Article 9 of the Council Directive of the EC of March 23, 1994 (94/9/EC), certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive. The examination and test results are recorded in the confidential report No. 14 203 145373.
- (9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:
EN 60079-0:2012 EN 60079-11:2012
- (10) If the sign "X" is placed after the certificate number, it indicates that the equipment or protective system is subject to special conditions for safe use specified in the schedule to this certificate.
- (11) This EC-type-examination certificate relates only to the design, examination and tests of the specified equipment in accordance to the Directive 94/9/EC. Further requirements of the Directive apply to the manufacturing process and supply of this equipment. These are not covered by this certificate.
- (12) The marking of the equipment or protective system must include the following:

 II (1) G [Ex ia Ga] IIC, II (1) D [Ex ia Da] IIIC, I (M1) [Ex ia Ma] I

TÜV NORD CERT GmbH, Langemarckstraße 20, 45141 Essen, notified by the central office of the countries for safety engineering (ZLS), Ident. Nr. 0044, legal successor of the TÜV NORD CERT GmbH & Co. KG Ident. Nr. 0032

The head of the notified body



Karl-Heinz Schwedt

Hanover office, Am TÜV 1, 30519 Hanover, Fon +49 (0)511 986 1455, Fax +49 (0)511 986 1590

This certificate may only be reproduced without any change, schedule included.
Excerpts or changes shall be allowed by the TÜV NORD CERT GmbH

(13) SCHEDULE

(14) EC-Type-Examination Certificate No. TÜV 14 ATEX 145373

(15) Description of equipment

The signal conditioning instruments type

VEGATOR TOR 141.A C/O/U X****

VEGATOR TOR 141.A C/O/U S****

VEGATOR TOR 142.A C/O/U *****

are used for the supply of passive, intrinsically safe 4 ... 20 mA two wire measuring sensors, the safe galvanic separation of the intrinsically safe circuits from all non-intrinsically safe circuits and the evaluation of the analogue transmitted measuring data.

The permissible ambient temperature range is -20 °C ... +60 °C.

Electrical data

Supply

U = 20 ... 253 V a. c./d. c.

(Terminals 16/17)

U_m = 253 V

Signal circuits

in type of protection „Intrinsic Safety“ Ex ia IIC, IIB, I
maximum values per circuit:

(Terminals 1/2, 4/5)

U_o = 22.4 V

I_o = 113.5mA

P_o = 636 mW

characteristic line: linear

Ex ia	IIC	IIB	I
max. permissible ext. inductance	0.5 mH	10 mH	10 mH
max. permissible ext. capacitance	0.095 µF	0.55 µF	1.2 µF

The maximum values of the tables are also allowed to be used up to the permissible limits as concentrated capacitances and as concentrated inductances.

The values for IIC and IIB are also permissible for explosive dust atmospheres.

Relay outputs

maximum values:

(Terminals 10/11/12, 13/14/15)

253 V a. c., 3A

60 V d. c., 1A

The intrinsically safe signal circuit is safe galvanically separated from the non-intrinsically safe circuits up to a peak value of the voltage of 375 V.

(16) The test documents are listed in the test report No. 14 203 145373.

(17) Special conditions for safe use

None

(18) Essential Health and Safety Requirements

no additional ones

