



Clinker silo

Reliable

Reliable measurement despite high temperatures

Cost effective

Optimal stocks enable continuous production


User friendly

Maintenance-free operation

Level measurement and point level detection in clinker silos

After the raw meal is burned, the emerging clinker of varying consistency is stored for further processing. The silos are filled and emptied through different openings. Continuous operation of the subsequent production processes is ensured by level measurement and point level detection.

[More details](#)



VEGAPULS 69

Level measurement with radar in clinker silos

- Exact measurement right to the bottom of the discharge funnel thanks to small beam angle
- High measurement certainty, unaffected by dust and temperature changes
- Maintenance-free through non-contact measurement

[Show Product](#)



VEGACAP 65

Capacitive point level detection in clinker silos

- Robust construction ensures a long service life
- Reliable measurement, unaffected by buildup
- Cut to length cable probes allow high flexibility

[Show Product](#)



VEGAPULS 69 Show Product	VEGACAP 65 Show Product
Measuring range - Distance 120 m	Measuring range - Distance -
Process temperature -40 ... 200 °C	Process temperature -50 ... 200 °C
Process pressure -1 ... 20 bar	Process pressure -1 ... 64 bar
Accuracy ± 5 mm / ± 0.2"	Version Cable ø 6 mm with screening tube without weight Cable ø 6 mm with screening tube and gravity weight Cable ø 6 mm with gravity weight Cable ø 8 mm with abrasion protection without weight Cable ø 8 mm with abrasion protection and gravity weight Cable ø 8 mm with gravity weight PA cable ø 12 mm with screening tube and gravity weight
Frequency 80 GHz	
Beam angle ≥ 3,5°	
Version with plastic horn antenna ø 80 mm Metal jacketed lens antenna	
Materials, wetted parts 316L PP PEEK	
Threaded connection G1½, 1½ NPT	Materials, wetted parts PTFE 316L PA PEEK Steel
Flange connection ≥ DN80, ≥ 3"	Threaded connection ≥ G1, ≥ 1 NPT
	Flange connection ≥ DN50, ≥ 2"
	Housing material Plastic Aluminium Stainless steel (precision casting) Stainless steel (electropolished)
	Protection rating IP66/IP68 (0,2 bar) IP66/IP67 IP66/IP68 (1 bar)
	Output Relay (DPDT) Contactless electronic switch Transistor (NPN/PNP) Two-wire