



Reliable

Reliable level measurement for trouble-free operation of the raw material stocks

Cost effective

Complete utilising of the silo without mechanical overload

User friendly

Easy installation in the container roof with exact alignment for optimum measurement accuracy

Raw material silo in the ethanol plant

Level measurement and point level detection in the grain silo

Ethanol is an additive used in gasoline. Through the use of renewable resources, the CO₂ emission of fuels is significantly improved and the consumption of crude oil reduced. In modern ethanol plants, raw materials such as grain, sugar cane or sugar beet are processed into alcohol and ethanol. The resulting by-products and residues are also completely utilized. The different types of grain used for ethanol production are stored in silos more than 20 m high. Reliable silo level measurement is essential to ensure continuous production supply is maintained.

[More details](#)



VEGAPULS 6X

Level measurement with radar in the grain silo

- Reliable measurement, even with changing media
- Easy mounting and setup thanks to installation from above
- Trustworthy measurement data even during filling

[Show Product](#)





VEGA VIB 62

Point level detection with vibrating level switch

- Wear and maintenance-free
- Easy to install and adjustment-free
- Reliable point level detection, even with changing media

[Show Product](#)

PRO	PRO
VEGAPULS 6X Show Product	VEGAVIB 62 Show Product
	
Measuring range - Distance 120 m	Process temperature -40 ... 150 °C
Process temperature -196 ... 450 °C	Process pressure -1 ... 6 bar
Process pressure -1 ... 160 bar	Version Detection of solids in water Suspension cable
Accuracy ± 1 mm	Materials, wetted parts 316L FEP PUR
Frequency 6 GHz 26 GHz 80 GHz	Threaded connection ≥ G1, ≥ 1 NPT
Beam angle ≥ 3°	Flange connection ≥ DN 32, ≥ 1½"
Materials, wetted parts PTFE PVDF 316L PP PEEK	Seal material CR, CSM
Threaded connection ≥ G¾, ≥ ¾ NPT	Housing material Plastic Aluminium Stainless steel (precision casting) Stainless steel (electropolished)
Flange connection ≥ DN20, ≥ ¾"	Protection rating IP66/IP68 (0,2 bar) IP66/IP67 IP66/IP68 (1 bar)
Hygienic fittings Clamp ≥ 1½" - DIN32676, ISO2852 Slotted nut ≥ 2", DN50 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A Hygienic flange connection ≥ DN50 DIN11864-2 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A DRD connection ø 65 mm SMS 1145 DN51	Output Relay (DPDT) Contactless electronic switch Transistor (NPN/PNP) Two-wire NAMUR