



Reliable

Reliable operation under all operating conditions

Cost effective

Maintenance-free operation of the facility

User friendly

Simple mounting and setup

Ore storage silo

Level measurement and point level detection in ore storage silos

Mined ore is transported via conveyor systems to large above ground or underground silos and stored there until it is used in production. A reliable level measurement is required to determine the contents of the silos.

[More details](#)



VEGAPULS 6X

Non-contact level measurement with radar in the ore storage silo

- Reliable measurement, unaffected by dust
- Easy alignment of the sensor via integrated swivelling holder and app for smartphone
- High plant availability, because wear and maintenance-free

[Show Product](#)





VEGACAP 65

Capacitive point level detection for overflow protection in the ore storage silo

- Reliable measurement despite buildup and dust
- Robust sensor construction for long service life
- Simple mounting and Setup

[Show Product](#)

PRO	PRO
VEGAPULS 6X Show Product	VEGACAP 65 Show Product
	
Measuring range - Distance 120 m	Measuring range - Distance -
Process temperature -196 ... 450 °C	Process temperature -50 ... 200 °C
Process pressure -1 ... 160 bar	Process pressure -1 ... 64 bar
Accuracy ± 1 mm	Version Cable ø 6 mm with screening tube without weight Cable ø 6 mm with screening tube and gravity weight Cable ø 6 mm with gravity weight Cable ø 8 mm with abrasion protection without weight Cable ø 8 mm with abrasion protection and gravity weight Cable ø 8 mm with gravity weight PA cable ø 12 mm with screening tube and gravity weight
Frequency 6 GHz 26 GHz 80 GHz	Materials, wetted parts PTFE 316L PA PEEK Steel
Beam angle ≥ 3°	Threaded connection ≥ G1, ≥ 1 NPT
Materials, wetted parts PTFE PVDF 316L PP PEEK	Flange connection ≥ DN50, ≥ 2"
Threaded connection ≥ G¾, ≥ ¾ NPT	Housing material Plastic Aluminium Stainless steel (precision casting) Stainless steel (electropolished)
Flange connection ≥ DN20, ≥ ¾"	Protection rating IP66/IP68 (0,2 bar) IP66/IP67 IP66/IP68 (1 bar)
Hygienic fittings Clamp ≥ 1½" - DIN32676, ISO2852 Slotted nut ≥ 2", DN50 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A Hygienic flange connection ≥ DN50 DIN11864-2 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A DRD connection ø 65 mm SMS 1145 DN51	Output Relay (DPDT) Contactless electronic switch Transistor (NPN/PNP) Two-wire