



Reliable

Reliable level measurement and protection against foam overflow

Cost effective

Continuous, maintenance-free operation of the digester

User friendly

Low maintenance costs and reliable gas production

Digester

Level measurement and point level detection of foam in the digester

The organic components of sewage sludge are decomposed under anaerobic conditions in heated, closed digestion tanks. In the process, combustible gases such as methane are released from the sludge. These are collected in a biogas tank and then converted into electricity and heat in cogeneration (CHP) plants. A level sensor controls the filling of the digester. To ensure that no foam gets into the gas system along with the collected gas, a point level sensor is used for monitoring.

More details



VEGAPULS 6X

Level measurement with radar for control of the filling process

- Maintenance-free operation through non-contact measurement
- Accurate and reproducible measurement data, independent of gas concentration and pressure fluctuations
- Reliable measurement, even with foam and density changes
- Wireless operation via Bluetooth with smartphone, tablet or PC

Show Product



VEGACAP 64

Detection of the conductive foam prevents it from entering the gas facility

- Reliable foam detection, even with different foam consistencies
- Unaffected by contamination and buildup
- Simple mounting and setup

Show Product



VEGATOR 141

Double channel signal conditioning instrument for level detection

- Simple adjustment of the switching point through a potentiometer
- Clearly visible switching status via LED
- Simple installation through carrier rail mounting as well as detachable, coded terminals

Show Product



VEGATRENN 141

Separator for the optimum supply of power to the connected sensors

- On-site diagnostics for direct display of status via LEDs
- Simple parametrization interface using the HART sockets for user-friendly operation
- Galvanic separation of sensors and PLC is secured

Show Product



PRO

VEGAPULS 6X
[Show Product](#)

Measuring range - Distance
 120 m

Process temperature
 -196 ... 450 °C

Process pressure
 -1 ... 160 bar

Accuracy
 ± 1 mm

Frequency
 6 GHz
 26 GHz
 80 GHz

Beam angle
 $\geq 3^\circ$
Materials, wetted parts
 PTFE
 PVDF
 316L
 PP
 PEEK

Threaded connection
 $\geq G\frac{3}{4}$, $\geq \frac{3}{4}$ NPT

Flange connection
 $\geq DN20$, $\geq \frac{3}{4}$ "

Hygienic fittings
 Clamp $\geq 1\frac{1}{2}$ " - DIN32676, ISO2852
 Slotted nut ≥ 2 ", DN50 - DIN 11851
 Varivent $\geq DN25$
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 Hygienic screw connections $\geq DN50$ tube $\varnothing 53$ -
 DIN11864-1-A
 Hygienic flange connection $\geq DN50$ DIN11864-2
 Hygienic clamp connection $\geq DN50$ pipe $\varnothing 53$ - DIN11864-
 3-A
 DRD connection $\varnothing 65$ mm
 SMS 1145 DN51

PRO

VEGACAP 64
[Show Product](#)

Measuring range - Distance
 -

Process temperature
 -50 ... 200 °C

Process pressure
 -1 ... 64 bar

Version
 PTFE insulation

Materials, wetted parts
 PTFE
 316L
 Alloy C22 (2.4602)
 Steel C22.8

Threaded connection
 $\geq G\frac{3}{4}$, $\geq \frac{3}{4}$ NPT

Flange connection
 $\geq DN25$, ≥ 1 "

Seal material
 no media contact

Housing material
 Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

Protection rating
 IP66/IP68 (0,2 bar)
 IP66/IP67
 IP66/IP68 (1 bar)

VEGATOR 141
[Show Product](#)

Protection rating
 IP20

Input
 1 x 4 ... 20 mA sensor input

Output
 1 x operating relay (SPDT)
 Optionally 1 x fail safe relay output (SPDT)

Ambient temperature
 -20 ... 60 °C

Signal input (specify)
 4 ... 20 mA

Signal output (specify)
 Operating relay
 Fail safe relay

VEGATRENN 141
[Show Product](#)



Protection rating

IP20

Input

1 x 4 ... 20 mA/HART sensor input

Output

1 x 4 ... 20 mA

Ambient temperature

-20 ... 60 °C