



#### Reliable

High operational reliability through the use of chemically resistant materials

#### Cost effective

Optimal storage through reliable measurement

#### User friendly

Simple setup and commissioning

## Storage tanks for additives

### Level measurement and point level detection in storage tanks for additives

For many processes, additives such as sulfuric or hydrochloric acid are required. These are kept ready for use in storage tanks. Level measurement is needed here to ensure availability of the additives.

[More details](#)



#### VEGAPULS 6X

Non-contact level measurement with radar in storage tanks

- Exact measuring results, independent of media properties
- Highly corrosion resistant materials ensure a long service life
- Maintenance-free operation through non-contact measuring method

[Show Product](#)



#### VEGASWING 63

Vibrating level switch as overflow protection in storage tanks

- Product-independent switching point ensures exact detection of limit level
- Simple setup without adjustment
- Test button for easy checking of the measuring instrument during operation

[Show Product](#)

PRO

**VEGAPULS 6X**[Show Product](#)**Measuring range - Distance**

120 m

**Process temperature**

-196 ... 450 °C

**Process pressure**

-1 ... 160 bar

**Accuracy**

± 1 mm

**Frequency**

6 GHz

26 GHz

80 GHz

**Beam angle**

≥ 3°

**Materials, wetted parts**

PTFE

PVDF

316L

PP

PEEK

**Threaded connection**

≥ G¾, ≥ ¾ NPT

**Flange connection**

≥ DN20, ≥ ¾"

**Hygienic fittings**

Clamp ≥ 1½" - DIN32676, ISO2852

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

hygienic fitting with tension flange DN32

hygienic fitting F40 with compression nut

Hygienic screw connections ≥ DN50 tube ø53 -

DIN11864-1-A

Hygienic flange connection ≥ DN50 DIN11864-2

Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A

DRD connection ø 65 mm

SMS 1145 DN51

PRO

**VEGASWING 63**[Show Product](#)**Process temperature**

-50 ... 250 °C

**Process pressure**

-1 ... 64 bar

**Version**

Standard

Hygienic applications

with gas-tight leadthrough

with tube extension

with temperature adapter

**Materials, wetted parts**

PFA

316L

Alloy C22 (2.4602)

Alloy 400 (2.4360)

ECTFE

Enamel

**Threaded connection**

≥ G¾, ≥ ¾ NPT

**Flange connection**

≥ DN25, ≥ 1"

**Hygienic fittings**

Clamp ≥ 1" - DIN32676, ISO2852

Slotted nut ≥ 1½", ≥ DN40 - DIN 11851

Varivent ≥ DN25

hygienic fitting F40 with compression nut

SMS 1145 DN51

SMS DN38

Hygienic fittings ≥ DN25 - DIN11864-1-A

Hygienic flange connection DIN11864-2-A;

DN60(ISO)ø60,3

SMS socket piece DN38 PN6

**Seal material**

no media contact

**Housing material**

Plastic

Aluminium

Stainless steel (precision casting)

Stainless steel (electropolished)

**Protection rating**

IP66/IP67

IP66/IP68 (1 bar)

IP65