

Reliable

Certified materials according to FDA and EC 1935/2004 regulations

Cost effective

plics® concept: short delivery time, standardised operation

User friendly

One measurement, three measured values: level, pressure, temperature



Jam cooking kettle

Level measurement in a vacuum vessel

Deseeded fruits and other ingredients for the production of jam are weighed and placed in a cooking vessel and gently heated. The cooking process takes place in a closed vacuum boiler at a temperature of 65 °C to 85 °C, in order to maintain the product quality and preserve the fruits' flavours and colours. Pressure transmitters are deployed to closely monitor the vessel pressure and jam cooking process to ensure the setting point for the conserve is reached. One transmitter measures the head pressure, the other at the bottom of the tank measures the total pressure. The difference between the two is used to calculate the level with great precision.

More details



VEGABAR 83

Electronic differential pressure measurement for determining the level in the vacuum vessel

- Absolutely vacuum resistant, stable temperature properties
- METEC® measuring cell with patented, self-compensating action
- Accurate measured values, even during the heating phase

Show Product



Show Product Show Product Show Product Measuring range - Distance - Measuring range - Pressure -1 1000 bar Process temperature -40 200 °C Process pressure -1 1000 bar Accuracy 0.075 % Materials, wetted parts 316L Alloy C22 (2.4602) 316Ti (1.4571) Alloy C4 (2.4610) Threaded connection $\geq G'_{\lambda} \geq 1'$ Hygenic fittings Slotted nut $\geq DN25 - DIN 11851$ Varivent $\geq DN25$ $\geq DN25 \geq 1"$ Hygenic fittings Slotted nut $\geq DN25 - DIN 11851$ Varivent $\geq DN25$ hygienic fittings with tension flange DN32 Hygienic fittings $\geq DN33 - DIN11864-3-A$ Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53 Swagelok VCR screwing		VEGABAR 83
Measuring range - Pressure -1 1000 bar Process temperature -40 200 °C Process pressure -1 1000 bar Accuracy 0.075 % Materials, wetted parts 316L Alloy C22 (2.4602) 316Ti (1.4571) Alloy C4 (2.4610) Threaded connection ≥ G½, ≥ ½ NPT Flange connection ≥ DN25, ≥ 1" Hygenic fittings Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienic fittings Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienic fitting with tension flange DN32 Hygienic fittings ≥ DN33 - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53		
Measuring range - Pressure -1 1000 bar Process temperature -40 200 °C Process pressure -1 1000 bar Accuracy 0.075 % Materials, wetted parts 316L Alloy C22 (2.4602) 316Ti (1.4571) Alloy C4 (2.4610) Threaded connection ≥ G½, ≥ ½ NPT Flange connection ≥ DN25, ≥ 1" Hygenic fittings Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienic fittings Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienic fitting with tension flange DN32 Hygienic fittings ≥ DN33 - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53		•••
-1 1000 bar Process temperature -40 200 °C Process pressure -1 1000 bar Accuracy 0.075 % Materials, wetted parts 316L Alloy C22 (2.4602) 316Ti (1.4571) Alloy C4 (2.4610) Threaded connection $\ge G'_{2,} \ge 1'_{2}$ NPT Flange connection $\ge DN25, \ge 1"$ Hygenic fittings Slotted nut $\ge DN25$ - DIN 11851 Varivent $\ge DN25$ hygienic fitting with tension flange DN32 Hygienic flange connection $\ge DN50$ DIN11864-2 SMS 1145 DN51 SMS DN38 Hygienic fittings $\ge DN33$ - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr φ 53	Measuring ran -	ige - Distance
-40 200 °C Process pressure -1 1000 bar Accuracy 0.075 % Materials, wetted parts 316L Alloy C22 (2.4602) 316Ti (1.4571) Alloy C4 (2.4610) Threaded connection ≥ G $\frac{1}{2}$, ≥ $\frac{1}{2}$ NPT Flange connection ≥ DN25, ≥ 1" Hygenic fittings Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienic flange connection ≥ DN50 DIN11864-2 SMS 1145 DN51 SMS DN38 Hygienic fittings ≥ DN33 - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53	-	ige - Pressure
-1 1000 bar Accuracy 0.075 % Materials, wetted parts 316L Alloy C22 (2.4602) 316Ti (1.4571) Alloy C4 (2.4610) Threaded connection $\geq G/_2, \geq 1/_2$ NPT Flange connection $\geq DN25, \geq 1"$ Hygenic fittings Slotted nut $\geq DN25$ - DIN 11851 Varivent $\geq DN25$ hygienic fitting with tension flange DN32 Hygienice flange connection $\geq DN50$ DIN11864-2 SMS 1145 DN51 SMS DN38 Hygienic fittings $\geq DN33$ - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53	-	erature
0.075 % Materials, wetted parts 316L Alloy C22 (2.4602) 316Ti (1.4571) Alloy C4 (2.4610) Threaded connection $\geq G'_{2}, \geq \frac{1}{2}$ NPT Flange connection $\geq DN25, \geq 1$ " Hygenic fittings Slotted nut $\geq DN25 - DIN 11851$ Varivent $\geq DN25$ hygienic fitting with tension flange DN32 Hygienice flange connection $\geq DN50$ DIN11864-2 SMS 1145 DN51 SMS DN38 Hygienic fittings $\geq DN33 - DIN11864-1-A$ Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53		sure
316L Alloy C22 (2.4602) 316Ti (1.4571) Alloy C4 (2.4610) Threaded connection ≥ G ¹ / ₂ , ≥ $\frac{1}{2}$ NPT Flange connection ≥ DN25, ≥ 1" Hygenic fittings Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienice flange connection ≥ DN50 DIN11864-2 SMS 1145 DN51 SMS DN38 Hygienic fittings ≥ DN33 - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53		
≥ G ¹ / ₂ , ≥ ¹ / ₂ NPT Flange connection ≥ DN25, ≥ 1" Hygenic fittings Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienice flange connection ≥ DN50 DIN11864-2 SMS 1145 DN51 SMS DN38 Hygienic fittings ≥ DN33 - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53	316L Alloy C22 (2.46 316Ti (1.4571)	02)
≥ DN25, ≥ 1" Hygenic fittings Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienice flange connection ≥ DN50 DIN11864-2 SMS 1145 DN51 SMS DN38 Hygienic fittings ≥ DN33 - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53		
Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienice flange connection ≥ DN50 DIN11864-2 SMS 1145 DN51 SMS DN38 Hygienic fittings ≥ DN33 - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53	-	ction
Varivent G125	Slotted nut ≥ DN Varivent ≥ DN2 hygienic fitting v Hygienice flang SMS 1145 DN5 SMS DN38 Hygienic fittings Hyg. collar clan Hyg. clamp con Swagelok VCR	N25 - DIN 11851 5 with tension flange DN32 e connection ≥ DN50 DIN11864-2 51 s ≥ DN33 - DIN11864-1-A np adapter DN40PN40 DIN11864-3-A nection DIN11864-3-A; DN50 Rohr ø53
Seal material	Seal material	

