

Reliable

Reliable measurement, unaffected by media properties

Cost effective

Long service life ensures uninterrupted operation for extended periods

User friendly

Non-contact measurement through glass

Agitating tank

Level measurement and point level detection in an agitating tank

In the pharmaceutical industry, numerous liquids with widely different properties are required. Liquid intermediate products must be made available and held ready for further processes. To ensure smooth, continuous production, reliable level measurement and point level detection are essential.

[More details](#)



VEGAPULS 6X

Non-contact level measurement with radar in agitating tanks for raw and intermediate products

- Reliable measurement through inspection glass, independent of medium
- Wide dynamic range allows measurement even with slightly slanted windows
- Instrument ensures consistently reliable measurement, unaffected by temperature fluctuations and gas phases

[Show Product](#)





VEGASWING 63

Point level detection with vibrating level switches in agitating tanks for raw and intermediate products

- Level detector for all liquid media, regardless of viscosity
- Thanks to the exact switching point, the entire container capacity can be utilized and efficient production ensured despite changing media
- Simple setup and commissioning

[Show Product](#)

PRO	PRO
VEGAPULS 6X Show Product	VEGASWING 63 Show Product
	
Measuring range - Distance 120 m	Process temperature -50 ... 250 °C
Process temperature -196 ... 450 °C	Process pressure -1 ... 64 bar
Process pressure -1 ... 160 bar	Version Standard Hygienic applications with gas-tight leadthrough with tube extension with temperature adapter
Accuracy ± 1 mm	Materials, wetted parts PFA 316L Alloy C22 (2.4602) Alloy 400 (2.4360) ECTFE Enamel
Frequency 6 GHz 26 GHz 80 GHz	Threaded connection ≥ G¾, ≥ ¾ NPT
Beam angle ≥ 3°	Flange connection ≥ DN25, ≥ 1"
Materials, wetted parts PTFE PVDF 316L PP PEEK	Hygienic fittings Clamp ≥ 1" - DIN32676, ISO2852 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851 Varivent ≥ DN25 hygienic fitting F40 with compression nut SMS 1145 DN51 SMS DN38 Hygienic fittings ≥ DN25 - DIN11864-1-A Hygienic flange connection DIN11864-2-A; DN60(ISO)ø60,3 SMS socket piece DN38 PN6
Threaded connection ≥ G¾, ≥ ¾ NPT	Seal material no media contact
Flange connection ≥ DN20, ≥ ¾"	Housing material Plastic Aluminium Stainless steel (precision casting) Stainless steel (electropolished)
Hygienic fittings Clamp ≥ 1½" - DIN32676, ISO2852 Slotted nut ≥ 2", DN50 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A Hygienic flange connection ≥ DN50 DIN11864-2 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A DRD connection ø 65 mm SMS 1145 DN51	Protection rating IP66/IP67 IP66/IP68 (1 bar) IP65