



Reliable

Reliable monitoring of cooler process

Cost effective

Optimal cooling with minimum energy expenditure

User friendly


Maintenance-free measurement

Clinker cooler

Level and pressure measurement in the clinker cooler

To produce cement, the raw meal is burned to clinker in a long rotary kiln. After leaving the rotary kiln, the clinker has a temperature of up to +1300 °C and must be cooled down to a temperature of about +200 °C for further storage. To achieve this, the clinker bed is cooled with a continuous stream of air. Pressure monitoring is required in the lower part of the clinker cooler to make the cooling as effective as possible. The material height of the hot clinker, at over 1000 °C on the conveyor belt, also has to be reliably measured.

[More details](#)



VEGABAR 82

Pressure transmitter for pressure monitoring in the clinker cooler

- High plant availability thanks to rugged measuring cell
- Maintenance-free through front-flush mounting

[Show Product](#)





VEGAPULS 6X

Non-contact level measurement with radar in the clinker cooler

- Reliable measurement despite extremely high media temperatures
- Effective antenna cooling via blower or compressed air
- Long service life by utilising a temperature-resistant antenna system

[Show Product](#)

PRO	PRO
VEGABAR 82 Show Product	VEGAPULS 6X Show Product
	
Measuring range - Distance -	Measuring range - Distance 120 m
Measuring range - Pressure -1 ... 100 bar	Process temperature -196 ... 450 °C
Process temperature -40 ... 150 °C	Process pressure -1 ... 160 bar
Process pressure -1 ... 100 bar	Accuracy ± 1 mm
Accuracy 0.05 %	Frequency 6 GHz 26 GHz 80 GHz
Materials, wetted parts PVDF 316L Alloy C22 (2.4602) PP 1.4057 1.4410 Alloy C276 (2.4819) Duplex (1.4462) Titanium Grade 2 (3.7035)	Beam angle ≥ 3°
Threaded connection ≥ G¾, ≥ ¼ NPT	Materials, wetted parts PTFE PVDF 316L PP PEEK
Flange connection ≥ DN15, ≥ ½"	Threaded connection ≥ G¾, ≥ ¼ NPT
Hygienic fittings Clamp ≥ 1" - DIN32676, ISO2852 Slotted nut ≥ DN25 - DIN 11851 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut DRD connection ø 65 mm SMS 1145 DN51 SMS DN38 Swagelok VCR screwing Varivent G125 Varivent N50-40 for NEUMO BioControl D50 PN16 / 316L	Flange connection ≥ DN20, ≥ ¾"
Seal material EPDM FKM FFKM	Hygienic fittings Clamp ≥ 1½" - DIN32676, ISO2852 Slotted nut ≥ 2", DN50 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A Hygienic flange connection ≥ DN50 DIN11864-2 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A DRD connection ø 65 mm SMS 1145 DN51