



Reliable

High measuring accuracy despite low dielectric constants

Cost effective

Maintenance-free operation

User friendly

Sensor replacement even during operation thanks to cut-off valve

LPG spherical tank

Level and pressure monitoring in liquid gas tanks

LPG tanks are usually only accessible for service and maintenance work every few years during shut-down periods. In addition, the containers are mostly installed underground or covered with earth. The solution is a process independent measuring system that delivers safe and reliable readings despite low dielectric constants and low temperatures.

[More details](#)



VEGAPULS 6X

Level measurement with radar in spherical tanks

- Maintenance-free operation thanks to non-contact measuring principle
- High measuring accuracy even with low dielectric constants
- Very narrow signal focusing even in large measuring ranges
- The sensor is simple and easy to replace thanks to cut-off valve and isolation from process

[Show Product](#)



VEGABAR 83

Pressure transmitter for pressure monitoring in spherical tanks

- Universally applicable, fully welded measuring cells for direct connection to process
- A variety of process fittings always enables an appropriate adaptation to the container
- SIL conformity in accordance with IEC 61508, in a single-channel architecture up to SIL2 and in a multi-channel architecture up to SIL3
- Extremely robust measuring cells of Alloy, for higher safety during operation

[Show Product](#)

PRO

VEGAPULS 6X
[Show Product](#)

Measuring range - Distance

120 m

Process temperature

-196 ... 450 °C

Process pressure

-1 ... 160 bar

Accuracy

± 1 mm

Frequency

6 GHz

26 GHz

80 GHz

Beam angle

≥ 3°

Materials, wetted parts

PTFE

PVDF

316L

PP

PEEK

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN20, ≥ ¾"

Hygienic fittings

Clamp ≥ 1½" - DIN32676, ISO2852

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

hygienic fitting with tension flange DN32

hygienic fitting F40 with compression nut

Hygienic screw connections ≥ DN50 tube ø53 -

DIN11864-1-A

Hygienic flange connection ≥ DN50 DIN11864-2

Hygienic clamp connection ≥ DN50 pipe ø53 - DIN11864-

3-A

DRD connection ø 65 mm

SMS 1145 DN51

PRO

VEGABAR 83
[Show Product](#)

Measuring range - Distance

-

Measuring range - Pressure

-1 ... 1000 bar

Process temperature

-40 ... 200 °C

Process pressure

-1 ... 1000 bar

Accuracy

0.075 %

Materials, wetted parts

316L

Alloy C22 (2.4602)

316Ti (1.4571)

Alloy C4 (2.4610)

Threaded connection

≥ G½, ≥ ½ NPT

Flange connection

≥ DN25, ≥ 1"

Hygienic fittings

Clamp ≥ 1" - DIN32676, ISO2852

Slotted nut ≥ DN25 - DIN 11851

Varivent ≥ DN25

hygienic fitting with tension flange DN32

Hygienic flange connection ≥ DN50 DIN11864-2

SMS 1145 DN51

SMS DN38

Hygienic fittings ≥ DN33 - DIN11864-1-A

Hyg. collar clamp adapter DN40PN40 DIN11864-3-A

Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53

Swagelok VCR screwing

Varivent G125

Seal material

EPDM

FKM

FFKM

FEPM

VEGA