



Reliable

Reliable measurement, even in abrasive media

Cost effective

Standard sensors for all applications

User friendly

Simple setup and low maintenance

Storage silo for sugar and flour

Level and pressure measurement in storage silos

Flour and sugar are the basic ingredients for many food products and stored in silos up to 20 metres high. The filling and emptying is often performed by pneumatic systems that transport the media from the large external silos and deposit them in smaller holding vessels for further processing. The filling and emptying processes are controlled by reliable level measurement. Pressure monitoring is also needed in the pneumatic conveying pipelines.

[More details](#)



VEGAPULS 6X

Radar sensor for level measurement in the flour and sugar silos

- Precise focusing of the measurement signal, which means convenient installation almost anywhere on the silo roof is possible
- Accurate, reliable measurement data despite dust and noise
- Measurement even during filling, thereby ensuring continuous monitoring of the filling process via a control system

[Show Product](#)



VEGABAR 82

Pressure transmitter for monitoring pressure in the conveyor pipeline

- Wear-resistant CERTEC® ceramic measuring cell, insensitive to abrasion
- Maintenance-free through front-flush mounting
- Robust measuring cell for long service life

[Show Product](#)

PRO

PRO

VEGAPULS 6X[Show Product](#)**Measuring range - Distance**

120 m

Process temperature

-196 ... 450 °C

Process pressure

-1 ... 160 bar

Accuracy

± 1 mm

Frequency

6 GHz

26 GHz

80 GHz

Beam angle

≥ 3°

Materials, wetted parts

PTFE

PVDF

316L

PP

PEEK

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN20, ≥ ¾"

Hygienic fittings

Clamp ≥ 1½" - DIN32676, ISO2852

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

hygienic fitting with tension flange DN32

hygienic fitting F40 with compression nut

Hygienic screw connections ≥ DN50 tube ø53 -

DIN11864-1-A

Hygienic flange connection ≥ DN50 DIN11864-2

Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-

3-A

DRD connection ø 65 mm

SMS 1145 DN51

VEGABAR 82[Show Product](#)**Measuring range - Distance**

-

Measuring range - Pressure

-1 ... 100 bar

Process temperature

-40 ... 150 °C

Process pressure

-1 ... 100 bar

Accuracy

0.05 %

Materials, wetted parts

PVDF

316L

Alloy C22 (2.4602)

PP

1.4057

1.4410

Alloy C276 (2.4819)

Duplex (1.4462)

Titanium Grade 2 (3.7035)

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN15, ≥ ½"

Hygienic fittings

Clamp ≥ 1" - DIN32676, ISO2852

Slotted nut ≥ DN25 - DIN 11851

hygienic fitting with tension flange DN32

hygienic fitting F40 with compression nut

DRD connection ø 65 mm

SMS 1145 DN51

SMS DN38

Swagelok VCR screwing

Varivent G125

Varivent N50-40

for NEUMO BioControl D50 PN16 / 316L

Seal material

EPDM

FKM

FFKM