



**Reliable**

Reliable measurement ensured even in chlorinated water

**Cost effective**

Accurate detection of water in all tanks

**User friendly**


Simple mounting and maintenance-free operation

## Fresh water and pool water tanks

### Level measurement in fresh water and pool water tanks

Every yacht has different tanks on board for storing hot water, pool water and drinking water. For drinking water, an especially hygienic measuring system is required.

[More details](#)



#### VEGAWELL 52

Hydrostatic level measurement in the water tank

- Oil-free, ceramic-capacitive CERTEC® measuring cell
- Installation from the top or side
- High overload resistance
- Double seal withstands cleaning with chemical agents

[Show Product](#)



#### VEGABAR 82

Hydrostatic level measurement in the water tank

- On-site adjustment and display in one housing
- Oil-free, ceramic-capacitive CERTEC® measuring cell
- Side mounting

[Show Product](#)

PRO

PRO

**VEGAWELL 52**  
[Show Product](#)

**Measuring range - Pressure**  
 0 ... 60 bar

**Process temperature**  
 -20 ... 80 °C

**Process pressure**  
 -

**Accuracy**  
 0.1 %

**Materials, wetted parts**  
 PVDF  
 316L  
 Duplex (1.4462)  
 FEP  
 PE  
 1.4301  
 Titanium

**Seal material**  
 EPDM  
 FKM  
 FFKM

**Protection rating**  
 IP66/IP67  
 IP68

**Output**  
 4 ... 20 mA  
 Two-wire: 4 ... 20 mA/HART

**Ambient temperature**  
 -40 ... 80 °C

**VEGABAR 82**  
[Show Product](#)

**Measuring range - Distance**  
 -

**Measuring range - Pressure**  
 -1 ... 100 bar

**Process temperature**  
 -40 ... 150 °C

**Process pressure**  
 -1 ... 100 bar

**Accuracy**  
 0.05 %

**Materials, wetted parts**  
 PVDF  
 316L  
 Alloy C22 (2.4602)  
 PP  
 1.4057  
 1.4410  
 Alloy C276 (2.4819)  
 Duplex (1.4462)  
 Titanium Grade 2 (3.7035)

**Threaded connection**  
 $\geq G\frac{1}{4}$ ,  $\geq \frac{1}{4}$  NPT

**Flange connection**  
 $\geq DN15$ ,  $\geq \frac{1}{2}$ "

**Hygienic fittings**  
 Clamp  $\geq 1$ " - DIN32676, ISO2852  
 Slotted nut  $\geq DN25$  - DIN 11851  
 hygienic fitting with tension flange DN32  
 hygienic fitting F40 with compression nut  
 DRD connection  $\varnothing 65$  mm  
 SMS 1145 DN51  
 SMS DN38  
 Swagelok VCR screwing  
 Varivent G125  
 Varivent N50-40  
 for NEUMO BioControl D50 PN16 / 316L

**Seal material**  
 EPDM  
 FKM  
 FFKM