

**Reliable**

Highly accurate measurement of even low-density materials

Cost effective

Accurate measurement for optimal storage

User friendly


Installation in the double-walled container not necessary

Liquid hydrogen storage tank

Level measurement in a storage tank for liquid hydrogen

To store hydrogen with as little loss as possible, it must be cooled down to $-253\text{ }^{\circ}\text{C}$ at 1 bar so that it is in a liquid state. Liquid hydrogen is therefore stored in double-walled, insulated containers. In addition, the liquid hydrogen is overlaid with gaseous hydrogen. When liquid hydrogen leaves the insulated container, it evaporates immediately and heats up to room temperature. The level is measured reliably using the traditional differential pressure method.

[More details](#)



VEGADIF 85

Level measurement with differential pressure in the liquid hydrogen storage tank

- Reliable measurement thanks to diaphragm with gold coating
- Output of differential and absolute pressure through a second current output

[Show Product](#)

VEGADIF 85

[Show Product](#)**Measuring range - Pressure**

-40 ... 40 bar

Process temperature

-40 ... 105 °C

Process pressure

-1 ... 400 bar

Accuracy

0.065 %

Materials, wetted parts

316L

Alloy C276 (2.4819)

Gold

Superduplex (1.4410)

Threaded connection

¼ - 18 NPT

Flange connection

≥ DN32, ≥ 1½"

Seal material

EPDM

FKM

PTFE

Copper

Housing material

Plastic

Aluminium

Stainless steel (precision casting)

Stainless steel (electropolished)

Protection rating

IP66/IP68 (0,2 bar)

IP66/IP67

IP66/IP68 (1 bar)