



Reliable

Reliable measurement, independent of the process conditions

Cost effective

Ensures effective processing of the drilling mud

User friendly

Simple installation and setup from above

Shaker

Level measurement and point level detection in the shaker

Through the effects of strong vibration in the shaker, the liquid and solid components of the drilling mud returning from the borehole are separated from each other. The drilled rock and the sand are disposed of and the valuable drilling mud is fed back into the continuous drilling process. Level measurement and point level detection are absolutely necessary for effective processing of the drilling mud in the shaker.

[More details](#)



VEGAPULS 6X

Non-contact level measurement with radar in the shaker

- Accurate measurement, independent of media properties
- Reliable measurement, unaffected by vibration and buildup
- High equipment availability, as wear and maintenance-free

[Show Product](#)



VEGACAP 65

Capacitive level switch for point level detection in the shaker

- Long service life thanks to robust mechanical construction
- Reliable switching point ensured by large gravity weight
- Maintenance-free operation, as non-sensitive to soiling

[Show Product](#)

PRO

VEGAPULS 6X

[Show Product](#)



Measuring range - Distance
120 m

Process temperature
-196 ... 450 °C

Process pressure
-1 ... 160 bar

Accuracy
± 1 mm

Frequency
6 GHz
26 GHz
80 GHz

Beam angle
≥ 3°

Materials, wetted parts
PTFE
PVDF
316L
PP
PEEK

Threaded connection
≥ G¾, ≥ ¾ NPT

Flange connection
≥ DN20, ≥ ¾"

Hygienic fittings
Clamp ≥ 1½" - DIN32676, ISO2852
Slotted nut ≥ 2", DN50 - DIN 11851
Varivent ≥ DN25
hygienic fitting with tension flange DN32
hygienic fitting F40 with compression nut
Hygienic screw connections ≥ DN50 tube ø53 -
DIN11864-1-A
Hygienic flange connection ≥ DN50 DIN11864-2
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A
DRD connection ø 65 mm
SMS 1145 DN51

PRO

VEGACAP 65

[Show Product](#)



Measuring range - Distance
-

Process temperature
-50 ... 200 °C

Process pressure
-1 ... 64 bar

Version
Cable ø 6 mm with screening tube without weight
Cable ø 6 mm with screening tube and gravity weight
Cable ø 6 mm with gravity weight
Cable ø 8 mm with abrasion protection without weight
Cable ø 8 mm with abrasion protection and gravity weight
Cable ø 8 mm with gravity weight
PA cable ø 12 mm with screening tube and gravity weight

Materials, wetted parts
PTFE
316L
PA
PEEK
Steel

Threaded connection
≥ G1, ≥ 1 NPT

Flange connection
≥ DN50, ≥ 2"

Housing material
Plastic
Aluminium
Stainless steel (precision casting)
Stainless steel (electropolished)

Protection rating
IP66/IP68 (0,2 bar)
IP66/IP67
IP66/IP68 (1 bar)

Output
Relay (DPDT)
Contactless electronic switch
Transistor (NPN/PNP)
Two-wire