



### Reliable

Redundant measurement for highest safety standards

### Cost effective

Maintenance-free operation

### User friendly


Easy installation

## BTX separators

### Level measurement and point level detection in the BTX separators

Precise interface monitoring in refinery separators is critical to product quality because it confirms there is complete separation. For liquid-liquid interface in a BTX (benzene, toluene, xylene) separator, an accurate measurement helps control the quality of the separator's output and thus helps to extend equipment life in downstream units by avoiding potentially expensive operating issues.

[More details](#)



### VEGASWING 63

Vibrating level switch for overflow protection in BTX separators

- High level switch provides redundancy
- Maximum flexibility through switching point adaptable to the application
- Switching point is unaffected by media properties

[Show Product](#)



### VEGAFLEX 81 and magnetic level indicator

Guided wave radar sensor and magnetic level indicator for monitoring of the separation layer

- Guided wave radar and magnetic level indicator provide redundancy
- Dual measurement capability provides both total level and interface level
- Continuous reporting increases operational efficiency

[Show Product](#)

PRO

**VEGASWING 63**[Show Product](#)**Process temperature**

-50 ... 250 °C

**Process pressure**

-1 ... 64 bar

**Version**

Standard  
Hygienic applications  
with gas-tight leadthrough  
with tube extension  
with temperature adapter

**Materials, wetted parts**

PFA  
316L  
Alloy C22 (2.4602)  
Alloy 400 (2.4360)  
ECTFE  
Enamel

**Threaded connection**

≥ G¾, ≥ ¾ NPT

**Flange connection**

≥ DN25, ≥ 1"

**Hygienic fittings**

Clamp ≥ 1" - DIN32676, ISO2852  
Slotted nut ≥ 1½", ≥ DN40 - DIN 11851  
Varivent ≥ DN25  
hygienic fitting F40 with compression nut  
SMS 1145 DN51  
SMS DN38  
Hygienic fittings ≥ DN25 - DIN11864-1-A  
Hygienic flange connection DIN11864-2-A;  
DN60(ISO)ø60,3  
SMS socket piece DN38 PN6

**Seal material**

no media contact

**Housing material**

Plastic  
Aluminium  
Stainless steel (precision casting)  
Stainless steel (electropolished)

**Protection rating**

IP66/IP67  
IP66/IP68 (1 bar)  
IP65

PRO

**VEGAFLEX 81 and magnetic level indicator**[Show Product](#)**Measuring range - Distance**

75 m

**Process temperature**

-60 ... 200 °C

**Process pressure**

-1 ... 40 bar

**Accuracy**

± 2 mm

**Version**

Basic version for exchangeable cable ø 2; ø 4 mm  
Basic version for exchangeable rod ø 8 mm  
Basic version for exchangeable rod ø 12 mm  
Coax version ø 21.3 mm for ammonia application  
Coax version ø 21.3 mm with single hole  
Coax version ø 21.3 mm with multiple hole  
Coax version ø 42.2 mm with multiple hole  
Exchangeable rod ø 8 mm  
Exchangeable rod ø 12 mm  
Exchangeable cable ø 2 mm with gravity weight  
Exchangeable cable ø 4 mm with gravity weight  
Exchangeable cable ø 2 mm with centering weight  
Exchangeable cable ø 4 mm with centering weight  
Exchangeable cable ø 4 mm without weight  
exchangeable, PFA-coated cable ø4 mm with non-coated centering weight

**Materials, wetted parts**

PFA  
316L  
Alloy C22 (2.4602)  
Alloy 400 (2.4360)  
Alloy C276 (2.4819)  
Duplex (1.4462)  
304L

**Threaded connection**

≥ G¾, ≥ ¾ NPT

**Flange connection**

≥ DN25, ≥ 1"

**Seal material**

EPDM  
FKM  
FFKM  
Silicone FEP coated  
Borosilicate glass

**Housing material**

Plastic  
Aluminium

**VEGA**

Stainless steel (precision casting)  
Stainless steel (electropolished)