

Reliable

Certified hygienic design (3A/EHEDG) and approved materials according to EC 1935/2004 and FDA

Cost effective

Three instruments deliver four different measured values: pressure (head pressure and line pressure), level and temperature

User friendly

Standardized adjustment, process data storable and transferable

Reaction vessel

Level and pressure measurement and point level detection in multiproduct and multi-line production facilities

The measuring conditions inside a reaction vessel in a multi-product, multi-line production facility are characterized by changing media as well as widely fluctuating temperatures and pressures. Depending on the properties of the raw materials, either alloy, stainless steel or enamel lined vessels are used. Different components like stirrers, dryers and centrifuges also vary in each process. To ensure reliable operation and high productivity, both level and pressure have to be continuously measured and monitored.

More details



VEGADIF 85

Differential pressure transmitter for level measurement in the reaction vessels of a multi-product plant

- Reliable measurement independent of foam and internals
- Welded measuring cell ensures aseptic operation
- Additional measured values, e.g. static pressure

Show Product



VEGABAR 81

Pressure transmitter for measuring process pressure in the reaction vessels of a multi-product facility

- High overload and vacuum resistance
- Universally applicable at process temperatures up to +400° C, regardless of the process type (hatch)
- Diaphragm and flange materials are corrosion resistant even in the most aggressive media

Show Product



VEGASWING 61

Vibrating level switch for level detection in the reaction vessels of a multi-product facility

- Ideal level alarm for all liquid media, regardless of viscosity
- Thanks to the exact switching point, the entire tank capacity can be utilized, ensuring efficient production with changing media
- An enamel coating guarantees a long service life for the sensor and protects it against corrosive media

Show Product



VEGADIF 85 Show Product



Measuring range - Pressure

-40 ... 40 bar

Process temperature

-40 ... 105 °C

Process pressure

-1 ... 400 bar

Accuracy

0.065 %

Materials, wetted parts

316L

Alloy C276 (2.4819)

Gold

Superduplex (1.4410)

Threaded connection

1/4 - 18 NPT

Flange connection

≥ DN32, ≥ 1%"

Seal material

EPDM

FKM PTFE

Copper

Housing material

Plastic

Aluminium

Stainless steel (precision casting)

Stainless steel (electropolished)

Protection rating

IP66/IP68 (0,2 bar)

IP66/IP67

IP66/IP68 (1 bar)

VEGABAR 81 Show Product



Measuring range - Distance

-

Measuring range - Pressure

-1 ... 1000 bar

Process temperature

-90 ... 400 °C

Process pressure

-1 ... 1000 bar

Accuracy

0.2 % 0.1 %

Materials, wetted parts

Alloy C22 (2.4602)

Alloy 400 (2.4360)

Tantalum

Alloy C276 (2.4819)

Duplex (1.4462)

Titanium Grade 2 (3.7035)

1.4435

316/316L

Titanium Grade 7 (3.7235)

Threaded connection

≥ G½, ≥ ½ NPT

Flange connection

≥ DN25, ≥ 1"

Hygenic fittings

Clamp ≥ 1" - DIN32676, ISO2852

Slotted nut $\geq 1\frac{1}{2}$ ", \geq DN40 - DIN 11851

hygienic fitting with tension flange $\ensuremath{\mathsf{DN32}}$

hygienic fitting F40 with compression nut

Hygienice flange connection ≥ DN50 DIN11864-2

Hygienic fittings ≥ DN40 - DIN11864-1-A

Seal material

no media contact

VEGASWING 61

Show Product



Measuring range - Distance

-

Process temperature

-50 ... 250 °C

Process pressure

-1 ... 64 bar

Version

Standard

Hygienic applications

with gas-tight leadthrough

with temperature adapter

Materials, wetted parts

PFA

316L

Alloy C22 (2.4602)

Alloy 400 (2.4360) ECTFE

Enamel

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN25, ≥ 1"

Hygenic fittings

Clamp ≥ 1" - DIN32676, ISO2852

Slotted nut ≥ 1½", ≥ DN40 - DIN 11851

Varivent ≥ DN25

hygienic fitting F40 with compression nut

SMS 1145 DN51

SMS DN38

Hygienic fittings ≥ DN25 - DIN11864-1-A

Hygienic flange connection DIN11864-2-A;

DN60(ISO)ø60,3

SMS socket piece DN38 PN6

Seal material

no media contact

Housing material

Plastic

Aluminium

Stainless steel (precision casting)

Stainless steel (electropolished)

