



Reliable

Reliable operation despite extreme process conditions

Cost effective

Density measurement from the outside, without invasive changes to the pipe

User friendly


Optimized for the application, long-term maintenance-free measurement

Pipeline in the liquor recovery process

Density measurement in liquor recovery

The black liquor resulting from pulp cooking is regenerated and fed back into the digester. Liquor regeneration comprises several process steps. The processes take place at high temperatures and pressures; the media are aggressive and sometimes abrasive. Density measurement of the liquor in the pipelines is required for eco-friendly and energy-efficient process control.

[More details](#)



MINITRAC 31

Density measurement with radiation for energy-efficient liquor regeneration

- Enables automation of liquor regeneration process
- Non-contact measurement right through the vessel wall
- Maintenance-free operation

[Show Product](#)



VEGASOURCE 31

The source holder serves as a housing for the radiation capsule and protects it from external influences

- Minimal space requirements and simple mounting
- Operational reliability and safety with pneumatic shutter on the source holder
- Optimum shielding allows use without a restricted access area

[Show Product](#)

MINITRAC 31
[Show Product](#)

Measuring range - Distance

-

Process temperature

-40 ... 60 °C

Process pressure

-

Accuracy

0.1 %

Materials, wetted parts

No wetted material

Seal material

no media contact

Housing material
Aluminium
Stainless steel (precision casting)
Protection rating

IP66/IP67

Output
Profibus PA
Foundation Fieldbus
4 ... 20 mA/HART - four-wire
Ambient temperature

-40 ... 60 °C

VEGASOURCE 31
[Show Product](#)

Ambient temperature

-20 ... 80 °C