



#### Reliable

Reliable function under all operating conditions

#### Cost effective

Simple installation into existing vessels

#### User friendly


Maintenance-free operation

## Buffer tank

### Buffer tank pressure measurement and point level detection

In the smelter, above the fused salt electrolysis bath there are small buffer tanks that are pneumatically fed via pipelines. The alumina powder is dispensed into the melt bath in small quantities from these tanks. The filling of the buffer tank is controlled by the feed pressure. Full and empty alarms ensure optimal charging of the powder.

[More details](#)



#### VEGAWAVE 61

Vibrating level switches as full and empty detectors in buffer tanks

- Reliable function in spite of buildup
- Long service life ensured by very robust construction
- Simple setup without adjustment

[Show Product](#)





#### VEGABAR 82

Pressure transmitter for monitoring pressure in the feed pipe

- High durability thanks to CERTEC® ceramic measuring cell
- Measurement immune to abrasion and buildup
- High operational reliability through SIL2 approval

[Show Product](#)

PRO	PRO
<b>VEGAWAVE 61</b> <a href="#">Show Product</a>	<b>VEGABAR 82</b> <a href="#">Show Product</a>
	
<b>Measuring range - Distance</b> -	<b>Measuring range - Distance</b> -
<b>Process temperature</b> -50 ... 250 °C	<b>Measuring range - Pressure</b> -1 ... 100 bar
<b>Process pressure</b> -1 ... 25 bar	<b>Process temperature</b> -40 ... 150 °C
<b>Version</b> Standard Detection of solids in water with temperature adapter	<b>Process pressure</b> -1 ... 100 bar
<b>Materials, wetted parts</b> 316L	<b>Accuracy</b> 0.05 %
<b>Threaded connection</b> ≥ G1½, ≥ 1½ NPT	<b>Materials, wetted parts</b> PVDF 316L Alloy C22 (2.4602) PP 1.4057 1.4410 Alloy C276 (2.4819) Duplex (1.4462) Titanium Grade 2 (3.7035)
<b>Flange connection</b> ≥ DN50, ≥ 2"	
<b>Hygienic fittings</b> Clamp ≥ 2", DN50 - DIN32676, ISO2852	
<b>Seal material</b> no media contact	
<b>Housing material</b> Plastic Aluminium Stainless steel (precision casting) Stainless steel (electropolished)	<b>Threaded connection</b> ≥ G¾, ≥ ¾ NPT
	<b>Flange connection</b> ≥ DN15, ≥ ½"
	<b>Hygienic fittings</b> Clamp ≥ 1" - DIN32676, ISO2852 Slotted nut ≥ DN25 - DIN 11851 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut DRD connection ø 65 mm SMS 1145 DN51 SMS DN38 Swagelok VCR screwing Varivent G125 Varivent N50-40 for NEUMO BioControl D50 PN16 / 316L
	<b>Seal material</b> EPDM FKM FFKM