



Reliable

Reliable measurement ensures a continuous supply of fuel

Cost effective

Exact content measurement reduces logistics costs

User friendly

Maintenance-free operation

Silo for solid fuels

Level measurement and point level detection in silos for solid fuels

Large amounts of energy are needed to burn clinker in rotary kilns. Apart from conventional energy sources such as gas, oil and coal, solid substitute fuels such as dried sewage sludge, old tires or meat and bone meal are increasingly being used. Since the required amounts of energy represent a significant cost factor in cement production, exact level measurement of the solid fuels is essential.

[More details](#)



VEGAPULS 6X

Level measurement with radar in silos for solid fuels

- High measurement certainty, independent of product properties
- Exact measurement to the bottom of the discharge funnel thanks to small beam angle
- Very good signal focusing reduces interfering reflections

[Show Product](#)



VEGAWAVE 62

Overfill protection with vibrating level switch in silos for solid fuels

- Reliable function through product-independent switching point
- Immune to buildup
- Very robust construction minimizes maintenance costs

[Show Product](#)

PRO

VEGAPULS 6X
[Show Product](#)

Measuring range - Distance
 120 m

Process temperature
 -196 ... 450 °C

Process pressure
 -1 ... 160 bar

Accuracy
 ± 1 mm

Frequency
 6 GHz
 26 GHz
 80 GHz

Beam angle
 ≥ 3°

Materials, wetted parts
 PTFE
 PVDF
 316L
 PP
 PEEK

Threaded connection
 ≥ G¾, ≥ ¾ NPT

Flange connection
 ≥ DN20, ≥ ¾"

Hygienic fittings
 Clamp ≥ 1½" - DIN32676, ISO2852
 Slotted nut ≥ 2", DN50 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 Hygienic screw connections ≥ DN50 tube ø53 -
 DIN11864-1-A
 Hygienic flange connection ≥ DN50 DIN11864-2
 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-
 3-A
 DRD connection ø 65 mm
 SMS 1145 DN51

PRO

VEGAWAVE 62
[Show Product](#)

Measuring range - Distance
 -

Process temperature
 -40 ... 150 °C

Process pressure
 -1 ... 6 bar

Version
 Detection of solids in water
 Suspension cable

Materials, wetted parts
 316L
 FEP
 PUR

Threaded connection
 ≥ G1½, ≥ 1½ NPT

Flange connection
 ≥ DN50, ≥ 2"

Seal material
 CR, CSM

Housing material
 Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

Protection rating
 IP66/IP68 (0,2 bar)
 IP66/IP67
 IP66/IP68 (1 bar)