



#### Reliable

High measurement certainty thanks to media-independent measurement

#### Cost effective

Reliable measurement ensures continuous production

#### User friendly

No dismantling of sensor necessary when changing the container, as measurement is possible right through the BigBag

## Flexible Intermediate Bulk Container (Bulk bag, BigBag)

### Level measurement in a Flexible Intermediate Bulk Container (Bulk Bag)

Granular raw materials are delivered and stored in Flexible Intermediate Bulk Containers (FIBC) also known as 'Bulk Bags' or 'BigBags'. The raw materials are fed to the various process stages via conveyor belts or pneumatic lines. To ensure reliable supply to production, the levels in these FIBC's need to be continuously monitored.

[More details](#)



#### VEGAPULS 6X

Non-contact level measurement with radar in a FIBC

- Strong focusing of radar beam enables reliable measurement despite steel frame thanks to 80-GHz technology
- Due to the wide dynamic range, the measurement is completely independent of the medium
- Non-contact measurement allows the changing of BigBags without dismantling the sensor

[Show Product](#)



#### VEGADIS 81

External display and adjustment unit for plics® sensors

- User-friendly display can be used in accessible places
- Simple operation via four keys and clearly structured menu
- Convenient connection directly to the sensor without further measures

[Show Product](#)



**VEGAPULS 6X**  
[Show Product](#)


**Measuring range - Distance**  
120 m

**Process temperature**  
-196 ... 450 °C

**Process pressure**  
-1 ... 160 bar

**Accuracy**  
± 1 mm

**Frequency**  
6 GHz  
26 GHz  
80 GHz

**Beam angle**  
≥ 3°

**Materials, wetted parts**  
PTFE  
PVDF  
316L  
PP  
PEEK

**Threaded connection**  
≥ G¾, ≥ ¾ NPT

**Flange connection**  
≥ DN20, ≥ ¾"

**Hygienic fittings**  
Clamp ≥ 1½" - DIN32676, ISO2852  
Slotted nut ≥ 2", DN50 - DIN 11851  
Varivent ≥ DN25  
hygienic fitting with tension flange DN32  
hygienic fitting F40 with compression nut  
Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A  
Hygienic flange connection ≥ DN50 DIN11864-2  
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A  
DRD connection ø 65 mm  
SMS 1145 DN51

**VEGADIS 81**  
[Show Product](#)


**Housing material**  
Plastic  
Aluminium  
Stainless steel (precision casting)

**Protection rating**  
IP66/IP67

**Ambient temperature**  
-20 ... 70 °C

**Signal input (specify)**  
plics sensor (serial)

**Signal output (specify)**  
Display